Serial No. 10/769,753

AMENDMENTS TO THE CLAIMS

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with <u>underlining</u> and deleted text with <u>strikethrough</u>. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 5, 6, 8, and 9 to read as follows:

1. (CURRENTLY AMENDED) A multi-beam laser scanning unit for scanning a-multiple laser beambeams onto a photoreceptor medium, comprising:

a plurality of laser sources each emitting a laser beam;

a collimating lens converting collimating the laser beam into a parallel raybeams;

a polygon mirror deflecting the converted collimated laser-beam from the collimating lens beams;

a f-θ lens focusing the deflected laser beam<u>beams</u> onto the photoreceptor medium:

a transparent member disposed between the f- θ lens and the photoreceptor medium, and having a thickness varying depending on a height thereof perpendicular to a direction where the laser beam passes beams pass through the transparent member; and

a movable member varying the height of the transparent member with respect to the plurality of laser sources,

wherein the transparent member has an inclined lower side inclined with respect to a scanning direction of the laser beambeams, and the movable member has an inclined surface inclined with respect to the inclined lower side of the transparent member.

- 2. (CANCELLED)
- 3. (CANCELLED)

- 4. (PREVIOUSLY PRESENTED) The multi-beam laser scanning unit of claim 1, further comprising an elastic member formed at an upper side of the transparent member, for pressing the transparent member.
- 5. (CURRENTLY AMENDED) The multi-beam laser scanning unit of claim 1, wherein the transparent member has a triangular cross-section in the direction where the laser beam passes-beams pass through the transparent member.
- 6. (CURRENTLY AMENDED) The multi-beam laser scanning unit of claim 1, wherein the transparent member has a trapezoidal cross-section in the direction where the laser beam passes through the transparent member.
- 7. (ORIGINAL) The multi-beam laser scanning unit of claim 1, wherein the transparent member has an optical refractivity of at least 1.
 - 8. (CURRENTLY AMENDED) An image forming apparatus, comprising:

a transparent member disposed between an f-0 lens and a photoreceptor medium, having a thickness varying depending on a height thereof perpendicular to a direction of the laser beambeams as the laser beam passes beams pass through the transparent member, and having an inclined lower side inclined with respect to a scanning direction of the laser beambeams; and

a movable member having an inclined surface inclined with respect to the inclined lower side of the transparent member and varying the height of the transparent member with respect to sources of the laser beambeams.

- 9. (CURRENTLY AMENDED) An image forming apparatus, comprising:
 - a plurality of laser sources each emitting a laser beam;
- a f-θ lens focusing onto a photoreceptor medium the laser beambeams after deflection of the laser beambeams by a polygon mirror;
 - a transparent member disposed between the f-θ lens and the photoreceptor

Serial No. 10/769,753

medium, having a thickness varying depending on a height thereof perpendicular to a direction of the laser beam passing beams pass through the transparent member, and having an inclined lower side inclined with respect to a scanning direction of the laser beambeams; and

a movable member varying the height of the transparent member with respect to the plurality of laser sources and having an inclined surface inclined with respect to the inclined lower side of the transparent member.